

## PROFIT TECHNOLOGY

WITH THE POWER OF OUR **BSVI** RANGE



Gross Vehicle Weight - GVW

| recinical Specifications       | 3532GW  |
|--------------------------------|---|
| Vehicle Dimensions             |   |
| Wheel Base (mm)                | 5175  |
| Cabin                          | Day Cabin   |
| Loadbody (Cu.m)                | 18 / 19 Cu.m Scoop (Fully Built)                            |
|                                | 23 / 27 Cu.m Box (Fully Built)                              |
| Overall Length (mm)            | 8085  |
| Overall Width (mm)             | 2490  |
| Overall Height (mm) ( CBC)     | 2962  |
| Front Overhang (mm)            | 1485  |
| Rear Overhang (mm)             | 750   |
| Ground Clearance (mm)          | 359   |
| Engine                         |   |
| Engine Model                   | OM 926  |
| Maximum Power, kW              | 236kW @ 2200 rpm  |
| Maximum Torque, Nm             | 1250 <b>N</b> m @ 1200 - 1600 rpm                           |
| No. of cylinders, cc           | 6, 7200   |
| Emission Standard              | Bharat Stage VI - OBD-2                                     |
| Transmission                   |   |
| Gear Box Model & Type          | G 131, 9F+1R, Mechanical, Synchromesh Gears                 |
| Clutch Type                    | Single Dry Plate, Hydraulic Control                         |
| Clutch Dia, Wear (mm)          | 430, 4.5  |
| Power Take Off                 | Standard  |
| Axle                           |   |
| Front Axle                     | IF 7.5  |
| Rear Axle                      | MT 610 Hub Reduction  |
| Rear Axle Ratio                | 6.18  |
| Chassis Frame & Suspension     |   |
| Frame Section (D X W X T) mm   | 288 x 70 x 9  |
| Front Suspension               | Parabolic Type Leaf Spring with 2 Hydraulic Shock Absorbers |
| Rear Suspension                | Bogie Suspension  |
| Anti-roll Bar                  | Front: Standard / Rear RA2: Standard                        |
| Brakes                         |   |
| Service Brake                  | Pneumatic Foot Operated, Dual Line with ABS                 |
| Parking Brake                  | Pneumatically Operated Hand Control Valve                   |
| Front Brake Size (mm) & Type   | Ø 410 drum  |
| Rear Brake Size (mm) & Type    | Ø 410 drum  |
| Steering                       |   |
| Steering Type                  | Hydraulic Power Assisted                                    |
| Fuel & Electrical System       |   |
| Fuel Tank / Filling Capacity   | 330L / 310L, 215L / 200L                                    |
| Adblue Tank / Filling Capacity | 43L / 36L   |
| Battery Capacity               | 120Ah   |
| Voltage                        | 24V   |
| Performance                    |   |
| Maximum Gradeability %         | 58%   |
| Maximum Geared Speed kmph      | 60 kmph   |
| TCD                            | 19.4 m  |
| Tyres                          |   |
| Pattern & Size                 | 12 X 20 – 18PR (Mine lug)                                   |
| W ' 14                         |   |

35000 kgs